

Leica DISTO™ D410 Laser Distance Meter

Precise targeting and simple outdoor measurement!



The new Leica DISTO™ D410 stands for easy and effortless outdoor distance measurement. With its digital Pointfinder you can target and measure distances even when you cannot see the laser dot. Accurate targeting provides reliable results, especially over long distances and in glaring sunshine. Due to the protection class IP 65, it always delivers reliable results. Furthermore all functions can be clearly seen on the display screen and simply selected.

Features

- Pointfinder with 4x zoom
- Large colour display screen
- IP 65 water jet protection and dust-tight
- Smart Horizontal Mode™



Simple and precise targeting - Pointfinder with 4x zoom

With the Pointfinder, the Leica DISTO™ D410 takes measurements with perfect accuracy and in unfavorable light conditions. This is a decisive advantage when working outside in sunny weather. Even if the red laser point is no longer visible to the naked eye, the target can be seen exactly in the crosshairs on the display.



Tough and easy to clean

The housing and keypad are specially sealed against water and dust. Cleaning under running water is also no problem. Furthermore the laser distance meter can be used in all weather conditions, being dust-proof and water jet protected (IP 65).



Smart Horizontal Mode

Even if obstructions such as walls, hedges or people stand in the direction of the target, the Leica DISTO™ D410 quickly comes up with an accurate result thanks to the "Smart Horizontal Mode". One measurement is enough for the required horizontal distance to appear on the display.



Highest reliability

The range and accuracy of the Leica DISTO™ D410 are tested to ISO-16331-1. That means it has a long range of 150 m and achieves an extremely high accuracy of ± 1 mm, not only under perfect laboratory conditions, but also in everyday use on site.



Technical Specifications

Typical measuring accuracy	± 1 mm
Range	up to 150 m
Measuring units	m, ft, in, yd
X-Range Power Range Technology™	•
Distance in m	10, 50, 100 m
Ø of the laser dot in mm	6, 30, 60 mm
Tilt sensor measuring range	360°
Pointfinder with 4x zoom	•
Memory	30 displays
Free App	•
Measurements per set of batteries	up to 5000**
Multifunctional end-piece	automatic recognition
Batteries	type AA 2 × 1,5 V
Tripod thread	•
Protection class	IP65 – water jet protection and dust-tight
Dimensions	143 × 58 × 29 mm
Weight with batteries	198 g

Functions

Minimum / maximum measurements	•
Area / volume measurement	•
Triangle / room angle function	•
Painter function	•
Trapezium measurements	•
Pythagoras functions	•
Smart Horizontal Mode™	•
Stake-out function	a/b
Subtraction / addition	•

Packing List

- Leica DISTO™ D410 laser distance meter
- Holster
- Hand loop
- Batteries



Which instrument is the right one for me?



Technical Data	D1	D110	D2	X310	D410	D510	D810 touch	S910
Distance measurement	40m	60m	100m	120m	150m	200m	200m	300m
Minimum/maximum measurements	-	-	Y	Y	Y	Y	Y	Y
Area / volume measurements	-	Area	Y	Y	Y	Y	Y	Y
Triangle/room angle function	-	-	-	Y	-	Y	Y	Y
Painter function	-	-	Y	Y	Y	Y	Y	Y
Trapezium function	-	-	-	-	-	Y	Y	Y
Pythagoras functions	-	-	Y	Y	Y	Y	Y	Y
Tilt measurement	-	-	-	360°	-	360°	360°	360°
Smart Horizontal Mode	-	-	-	Y	Y	Y	Y	Y
Sloped object measurement	-	-	-	-	-	Y	Y	Y
Height tracking	-	-	-	Y	-	Y	Y	Y
Height profile measurements	-	-	-	-	-	Y	Y	Y
Stake-out function	-	-	a/a	a/b	a/b	a/b	a/b	a/b
Subtraction/addition	-	-	Y	Y	Y	Y	Y	Y
Pointfinder with 4x zoom	-	-	-	-	Y	Y	Y	Y
Camera function	-	-	-	-	-	-	Y	Y
Measure with the picture	-	-	-	-	-	-	Y	Y
Timer	-	-	Y	Y	Y	Y	Y	Y
Personalised favourites	-	-	-	-	Y	Y	Y	Y
Touch screen	-	-	-	-	-	-	Y	Y
Compass	-	-	-	-	-	-	Y	Y
Point-to-Point measurements	-	-	-	-	-	-	-	Y
Smart angle measurement	-	-	-	-	-	-	-	Y
Smart area measurement	-	-	-	-	-	-	-	Y
DXF data capture	-	-	-	-	-	-	-	Y
WLAN data transmission	-	-	-	-	-	-	-	Y
Bluetooth Smart	Y	Y	Y	-	-	Y	Y	Y



Distance Meter Specifications



Technical Data

	D1	D110	D2	X310
Measuring Accuracy	± 2.0 mm	± 2.0 mm	± 1.5 mm	± 1.0 mm
Range (From about 80 m, use target plate)	0.2 to 40m	0.2 to 60m	0.2 to 100m	0.05 to 120m
Power Range Technology	-	-	-	Y
X-Range Power Technology	Y	Y	Y	-
Distance in m	10 m	10, 50 m	10, 50, 100 m	10, 50, 100 m
Diameter of laser dot in mm	6 mm	6, 30 mm	6, 30, 60 mm	6, 30, 60 mm
Tilt sensor - Measuring Range	-	-	-	360°
Tilt sensor - Accuracy to the laser beam	-	-	-	±0.2°
Tilt sensor - Accuracy to the housing	-	-	-	±0.3°
Units in tilt sensor	-	-	-	0.0°, 0.0%
Smart Base Measuring Range - Horizontal	-	-	-	-
Smart Base Measuring Range - Vertical	-	-	-	-
Distance in m	-	-	-	-
Typical Tolerance of the P2P function	-	-	-	-
Levelling range	-	-	-	-
Levelling accuracy	-	-	-	-
Pointfinder with 4x zoom	-	-	-	-
Overview camera	-	-	-	-
Picture file format	-	-	-	-
Memory	-	-	10 results	20 displays
Memory for pictures	-	-	-	-
CAD data format	-	-	-	-
Memory for CAD files	-	-	-	-
Time delay release (timer)	-	-	Y	Y
Display illumination	Y	Y	Y	Y
Free software for Windows	Y	Y	Y	-
Free App	IOS / Android	IOS / Android	IOS / Android	-
Data interface*	Bluetooth SMART	Bluetooth SMART	Bluetooth SMART	-
Measurements per set of batteries	up to 10,000	up to 10,000	up to 10,000	up to 5,000
Service life of battery	up to 20 hours	up to 20 hours	up to 20 hours	up to 10 hours
Multifunctional end-piece	-	-	Y	Y
Tripod thread	-	-	-	Y
Batteries	AAA 2x1.5V	AAA 2x1.5V	AAA 2x1.5V	AAA 2x1.5V
Charging time	-	-	-	-
Protection class	IP54	IP54	IP54	IP65
Dimensions	115x43.5x23.5mm	120x37x23mm	116x44x26mm	122x55x31mm
Weight with batteries	87g	92g	100g	155g





Technical Data

	D410	D510	D810 touch	S910
Measuring Accuracy	± 1.0 mm	± 1.0 mm	± 1.0 mm	± 1.0 mm
Range (From about 80 m, use target plate)	0.05 to 150m	0.05 to 200m	0.05 to 200m	0.05 to 300m
Power Range Technology	Y	Y	Y	
X-Range Power Technology				Y
Distance in m	10, 50, 100 m	10, 50, 100 m	10, 50, 100 m	10, 50, 100 m
Diameter of laser dot in mm	6, 30, 60 mm	6, 30, 60 mm	6, 30, 60 mm	6, 30, 60 mm
Tilt sensor - Measuring Range	-	360°	360°	360°
Tilt sensor - Accuracy to the laser beam	-	+0.2°	-0.1° / +0.2°	-0.1° / +0.2°
Tilt sensor - Accuracy to the housing	-	±0.2°	±0.1°	±0.1°
Units in tilt sensor	-	0.0°, 0.00%	0.0°, 0.00%	0.0°, 0.00%
Smart Base Measuring Range - Horizontal	-	-	-	360°
Smart Base Measuring Range - Vertical	-	-	-	-40° to 80°
Distance in m	-	-	-	2, 5, 10m
Typical Tolerance of the P2P function	-	-	-	2, 5, 10mm
Levelling range	-	-	-	±5°
Levelling accuracy	-	-	-	±0.05°
Pointfinder with 4x zoom	Y	Y	Y	Y
Overview camera	-	-	Y	Y
Picture file format	-	-	.jpg	.jpg
Memory	30 displays	30 displays	30 displays	50 displays
Memory for pictures	-	-	80 Photos	80 Photos
CAD data format	-	-	-	.dxf
Memory for CAD files	-	-	-	20 files, 30 points ea
Time delay release (timer)	Y	Y	Y	Y
Display illumination	Y	Y	Y	Y
Free software for Windows	-	-	Y	Y
Free App	-	IOS / Android	IOS / Android	IOS / Android
Data interface*	-	Bluetooth SMART	Bluetooth SMART	Bluetooth SMART, WLAN
Measurements per set of batteries	up to 5,000	up to 5,000	up to 4,000	up to 4,000
Service life of battery	up to 10 hours	up to 10 hours	up to 8 hours	up to 8 hours
Multifunctional end-piece	Y	Y	Y	-
Tripod thread	Y	Y	Y	Smart Base
Batteries	AA 2x1.5V	AA 2x1.5V	Li-ion rechargeable	Li-ion rechargeable
Charging time	-	-	4h	4h
Protection class	IP65	IP65	IP54	IP54
Dimensions	143x58x29mm	143x58x29mm	164x61x31mm	164x61x32mm
Weight with batteries	198g	198g	238g	290g

