

Leica DISTO™ D1 Laser Distance Meter

Experience the difference!



At the touch of a button the Leica DISTO™ D1 measures heights, distances as well as niches quickly and reliably. Complicated or dangerous measurement situations, where ladders may be necessary, are now in the past. The functionality of the DISTO™ D1 can be extended with the Leica DISTO™ sketch app. With this app you can transfer measuring results to smart phones or tablets, process and forward them.

Features

- Bluetooth® Smart for data transfer to smart phones and tablets
- Free App Leica DISTO™ sketch
- 40 m range
- X-Range Power Technology
- Clear, illuminated 3 line display
- IP 54 dust and splash water protected



Measure with laser precision

At the touch of a button the Leica DISTO™ D1 measures precisely and reliably even over longer distances. It is easy to operate and can hit targets which are not directly accessible.



Just precise

One measurement is sufficient and the result can be easily read off the clearly arranged display. Adding subtotals, e.g. when measuring a niche, is no longer necessary.



Perfect documentation

With just a few clicks, the Leica DISTO™ D1 can be connected with the DISTO™ sketch app. Create sketches or photos and dimension them with the measurement results, which are transferred directly to your smart phone or tablet. Plans are even automatically completed with areas and circumferences.



Quality from the Pioneer

The compact, easy-to-use Leica DISTO™ D1 demonstrates the experience of many years and the quality from Leica Geosystems, the leading manufacturer of measuring devices.



Technical Specifications

Measuring Accuracy	± 2.0 mm
Range	0.2 to 40m
X-Range Power Technology	Y
Distance in m	10 m
Diameter of laser dot in mm	6 mm
Display illumination	Y
Free software for Windows	Y
Free App	IOS / Android
Data interface*	Bluetooth SMART
Measurements per set of batteries	up to 10,000
Service life of battery	up to 20 hours



Shipping List

- Leica DISTO™ D1
- Batteries

Bluetooth® Smart and Leica DISTO™ Sketch app



Extended functionality by pressing a button

The smart App "Leica DISTO™ sketch" is the ideal link between the Leica DISTO™ with Bluetooth® Smart and a smartphone or a tablet. It allows you to create and precisely dimension sketches and pictures. The files can then be sent directly to the office. This simplifies and speeds up work flow.



BAMR (Pty) Ltd, PO Box 23973, Claremont, 7735, South Africa
 Ph : 27 (0)21 683 2100, Fax : 27 (0)21 674 1485
 Email : sales@bamr.co.za Web : www.bamr.co.za

Which instrument is the right one for me?



Technical Data	D1	D110	D2	X310	D410	D510	D810 touch	S910
Distance measurement	40m	60m	100m	120m	150m	200m	200m	300m
Minimum/maximum measurements	-	-	Y	Y	Y	Y	Y	Y
Area / volume measurements	-	Area	Y	Y	Y	Y	Y	Y
Triangle/room angle function	-	-	-	Y	-	Y	Y	Y
Painter function	-	-	Y	Y	Y	Y	Y	Y
Trapezium function	-	-	-	-	-	Y	Y	Y
Pythagoras functions	-	-	Y	Y	Y	Y	Y	Y
Tilt measurement	-	-	-	360°	-	360°	360°	360°
Smart Horizontal Mode	-	-	-	Y	Y	Y	Y	Y
Sloped object measurement	-	-	-	-	-	Y	Y	Y
Height tracking	-	-	-	Y	-	Y	Y	Y
Height profile measurements	-	-	-	-	-	Y	Y	Y
Stake-out function	-	-	a/a	a/b	a/b	a/b	a/b	a/b
Subtraction/addition	-	-	Y	Y	Y	Y	Y	Y
Pointfinder with 4x zoom	-	-	-	-	Y	Y	Y	Y
Camera function	-	-	-	-	-	-	Y	Y
Measure with the picture	-	-	-	-	-	-	Y	Y
Timer	-	-	Y	Y	Y	Y	Y	Y
Personalised favourites	-	-	-	-	Y	Y	Y	Y
Touch screen	-	-	-	-	-	-	Y	Y
Compass	-	-	-	-	-	-	Y	Y
Point-to-Point measurements	-	-	-	-	-	-	-	Y
Smart angle measurement	-	-	-	-	-	-	-	Y
Smart area measurement	-	-	-	-	-	-	-	Y
DXF data capture	-	-	-	-	-	-	-	Y
WLAN data transmission	-	-	-	-	-	-	-	Y
Bluetooth Smart	Y	Y	Y	-	-	Y	Y	Y



Distance Meter Specifications



Technical Data

	D1	D110	D2	X310
Measuring Accuracy	± 2.0 mm	± 2.0 mm	± 1.5 mm	± 1.0 mm
Range (From about 80 m, use target plate)	0.2 to 40m	0.2 to 60m	0.2 to 100m	0.05 to 120m
Power Range Technology	-	-	-	Y
X-Range Power Technology	Y	Y	Y	-
Distance in m	10 m	10, 50 m	10, 50, 100 m	10, 50, 100 m
Diameter of laser dot in mm	6 mm	6, 30 mm	6, 30, 60 mm	6, 30, 60 mm
Tilt sensor - Measuring Range	-	-	-	360°
Tilt sensor - Accuracy to the laser beam	-	-	-	±0.2°
Tilt sensor - Accuracy to the housing	-	-	-	±0.3°
Units in tilt sensor	-	-	-	0.0°, 0.0%
Smart Base Measuring Range - Horizontal	-	-	-	-
Smart Base Measuring Range - Vertical	-	-	-	-
Distance in m	-	-	-	-
Typical Tolerance of the P2P function	-	-	-	-
Levelling range	-	-	-	-
Levelling accuracy	-	-	-	-
Pointfinder with 4x zoom	-	-	-	-
Overview camera	-	-	-	-
Picture file format	-	-	-	-
Memory	-	-	10 results	20 displays
Memory for pictures	-	-	-	-
CAD data format	-	-	-	-
Memory for CAD files	-	-	-	-
Time delay release (timer)	-	-	Y	Y
Display illumination	Y	Y	Y	Y
Free software for Windows	Y	Y	Y	-
Free App	IOS / Android	IOS / Android	IOS / Android	-
Data interface*	Bluetooth SMART	Bluetooth SMART	Bluetooth SMART	-
Measurements per set of batteries	up to 10,000	up to 10,000	up to 10,000	up to 5,000
Service life of battery	up to 20 hours	up to 20 hours	up to 20 hours	up to 10 hours
Multifunctional end-piece	-	-	Y	Y
Tripod thread	-	-	-	Y
Batteries	AAA 2x1.5V	AAA 2x1.5V	AAA 2x1.5V	AAA 2x1.5V
Charging time	-	-	-	-
Protection class	IP54	IP54	IP54	IP65
Dimensions	115x43.5x23.5mm	120x37x23mm	116x44x26mm	122x55x31mm
Weight with batteries	87g	92g	100g	155g





Technical Data

	D410	D510	D810 touch	S910
Measuring Accuracy	± 1.0 mm	± 1.0 mm	± 1.0 mm	± 1.0 mm
Range (From about 80 m, use target plate)	0.05 to 150m	0.05 to 200m	0.05 to 200m	0.05 to 300m
Power Range Technology	Y	Y	Y	
X-Range Power Technology				Y
Distance in m	10, 50, 100 m	10, 50, 100 m	10, 50, 100 m	10, 50, 100 m
Diameter of laser dot in mm	6, 30, 60 mm	6, 30, 60 mm	6, 30, 60 mm	6, 30, 60 mm
Tilt sensor - Measuring Range	-	360°	360°	360°
Tilt sensor - Accuracy to the laser beam	-	+0.2°	-0.1° / +0.2°	-0.1° / +0.2°
Tilt sensor - Accuracy to the housing	-	±0.2°	±0.1°	±0.1°
Units in tilt sensor	-	0.0°, 0.00%	0.0°, 0.00%	0.0°, 0.00%
Smart Base Measuring Range - Horizontal	-	-	-	360°
Smart Base Measuring Range - Vertical	-	-	-	-40° to 80°
Distance in m	-	-	-	2, 5, 10m
Typical Tolerance of the P2P function	-	-	-	2, 5, 10mm
Levelling range	-	-	-	±5°
Levelling accuracy	-	-	-	±0.05°
Pointfinder with 4x zoom	Y	Y	Y	Y
Overview camera	-	-	Y	Y
Picture file format	-	-	.jpg	.jpg
Memory	30 displays	30 displays	30 displays	50 displays
Memory for pictures	-	-	80 Photos	80 Photos
CAD data format	-	-	-	.dxf
Memory for CAD files	-	-	-	20 files, 30 points ea
Time delay release (timer)	Y	Y	Y	Y
Display illumination	Y	Y	Y	Y
Free software for Windows	-	-	Y	Y
Free App	-	IOS / Android	IOS / Android	IOS / Android
Data interface*	-	Bluetooth SMART	Bluetooth SMART	Bluetooth SMART, WLAN
Measurements per set of batteries	up to 5,000	up to 5,000	up to 4,000	up to 4,000
Service life of battery	up to 10 hours	up to 10 hours	up to 8 hours	up to 8 hours
Multifunctional end-piece	Y	Y	Y	-
Tripod thread	Y	Y	Y	Smart Base
Batteries	AA 2x1.5V	AA 2x1.5V	Li-ion rechargeable	Li-ion rechargeable
Charging time	-	-	4h	4h
Protection class	IP65	IP65	IP54	IP54
Dimensions	143x58x29mm	143x58x29mm	164x61x31mm	164x61x32mm
Weight with batteries	198g	198g	238g	290g

